

Article no.: Date of prin /ersion:	100VR1294 t: 22.01.2014 1.2	Revision date: 22.01.2014 Date of issue: 22.01.2014	EN Page:1 / 9					
SEC	TION 1: Identificatio	n of the substance/mixture and of	the company/undertaking					
Artic	luct identifiers: le no. (manufacturer / si tification of the substand							
		the substance or mixture and uses a	dvised against					
	Relevant identified uses:							
		Printing aids						
.3. Deta	ils of the supplier of tl	ne safety data sheet						
Sup A.M. RUC Lors		porter/downstream user/distributor): Telephone: +49 Telefax: +49.61						
Dept	. responsible for infor	mation:						
E-ma	ail:	info@ruco-inks	.com					
Eme	rgency telephone num rgency telephone: available during office l	+49.61 98.30 4	0					
SEC	TION 2: Hazards ide	ntification						
Clas	Classification of the substance or mixture Classification according to EC regulation 1272/2008 (CLP): This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].							
Acut Acut Skin Eye Skin	n. Liq. 3 / H226 e Tox. 4 / H302 e Tox. 4 / H332 Irrit. 2 / H315 Dam. 1 / H318 Sens. 1 / H317 T SE 2 / H371	flammable liquids Acute toxicity (oral) Acute toxicity (inhalative) skin corrosion/irritation Serious eye damage/eye irritation respiratory or skin sensitisation Specific target organ toxicity (single	Flammable liquid and vapour. Harmful if swallowed. Harmful if inhaled. Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May cause damage to organs.					
STO	T SE 3 / H335	exposure) Specific target organ toxicity (single exposure)	May cause respiratory irritation.					
STO	T SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.					
-	atic Chronic 2 / H411	Hazardous to the aquatic environment	nt Toxic to aquatic life with long lasting effects.					
	Classification according to Directive 67/548/EEC or 1999/45/EC							
	The preparation is dangerous in the sense of Directive 1999/45/EC.							
R10 Xi; R R43	37/38-41	Irritant	Flammable Irritating to respiratory system and skin. Risk o serious damage to eyes. May cause sensitization by skin contact.					
	51-53	Dangerous for the environment	Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.					
Xn; F	R68/20/21/22	Harmful	Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed.					
	el elements elling (CLP)							

Labelling (CLP) Hazard pictograms

RUCO

e no.: of print: on:	100VR1294 22.01.2014 1.2	Revision	n date: 22.01.20 issue: 22.01.201		Page	EN :2 / 9
				¥	Danger	
$\mathbf{\mathbf{\nabla}}$	\sim				Danger	
Hazard st	atements:					
H226		ammable liquid a	and vapour.			
H302 + H3		armful if swallow				
H315		auses skin irritat				
H318		auses serious ey				
H317			rgic skin reactio	n.		
H371		ay cause damag				
H335		ay cause respira				
H336			ness or dizzines	S.		
H411			e with long lastir			
			e with long looti	ig checto.		
	ecautions:	on ourse from t	oot/oport/or	flomos/hat		aking
P210 P233				names/not s	urfaces No sm	oking.
P233 P240		eep container tig		ing couloms	at	
		Ground/bond container and receiving equipment. Use explosion-proof electrical equipment.				
P241				ipment.		
P242		se only non-spar	•	inat atatia di	abaraa	
P243			y measures aga	inst static dis	charge.	
P260 P261		o not breathe va		the neurolon	F0.1	
			ust/fume/gas/mis		lay.	
P264			bughly after hand		luot	
P270			r smoke when us		luci.	
P271 P272		•	or in a well-ven		und out of the we	vrknja og
P272 P273			•	u not be allo	ved out of the wo	nkplace.
P273 P280		oid release to th		alathing (a) (a	protoction/face n	rotaction
P200 P301 + P3					protection/face p	
P301 + P3			h with plenty of s			if you feel unwell.
						nated clothing. Rinse skin with
1 303 1 1		ater/shower.	iii). Remove/Tak			lated clothing. Rinse skin with
P304 + P3	340 IF	INHALED: Rem	ove victim to fre	sh air and ke	ep at rest in a po	sition comfortable for breathing.
P305 + P3	351 + P338 IF		e cautiously with			move contact lenses, if present a
P309 + P3				all a POISON	I CENTER or doo	ctor/physician.
P310			POISON CENT			
P312			ENTER or doctor			
P330		nse mouth.			-	
P332 + P3	813 If :	skin irritation occ	curs: Get medica	al advice/atte	ntion.	
P333 + P3	313 If :	skin irritation or	rash occurs: Ge	t medical adv	ice/attention.	
P362	Та	ake off contamination	ated clothing an	d wash it bef	ore reuse.	
P363	W	ash contaminate	ed clothing befor	e reuse.		
P370 + P3	378 In	case of fire: Use	e Extinguishing p	bowder or sa	nd for extinction.	
P391	Co	ollect spillage.				
P403 + P2			ntilated place. Ke		tightly closed.	
P403 + P2	235 St	ore in a well-ver	ntilated place. Ke	ep cool.		
P405		eep locked up.				
P501	Di	spose of conten	ts/container to ir	ndustrial incir	eration plant.	
contains:						
		ethanol				
		itan-1-ol				
	3-	(2-Aminoethylan	nino)propyltrime	thoxysilane		
Suppleme	ental Hazard in	nformation (EU)):			
	n.	^				

×

Xn Harmful

603-001-00-X

Article Date o Versio	of print:	100VR1294 22.01.2014 1.2		EN Page:3 / 9		
	¥_2	Ν	Dangerous for the environment			
	Hazard st	atements:				
	10		ammable			
	37/38	In	ritating to respiratory system and skin.			
	41		isk of serious damage to eyes.			
	43		ay cause sensitization by skin contact.	are advance offects in the acvetic		
	51/53 68/20/21/2	22 H	oxic to aquatic organisms, may cause long-to armful: possible risk of irreversible effects th			
	Safety pre		usid contact with alkin			
	24 26		void contact with skin. case of contact with eyes, rinse immediatel	v with plenty of water and seek m	edical advice	
	36/37/39		ear suitable protective clothing, gloves and			
	51		se only in well-ventilated areas.			
	61	A	void release to the environment. Refer to sp	ecial instructions/safety data shee	et.	
	contains:					
			ethanol			
			utan-1-ol			
	Special p		-(2-Aminoethylamino)propyltrimethoxysilane			
	n.a.		cerning the labelling of certain mixtures			
2.3.	Other haz	ards				
	SECTION	3. Compos	ition/ information on ingredients			
3.2.	Mixtures					
			ion (preparation)			
	Descriptio	on: S	olvent containing resin solution			
	Hazardou	s ingredients	:			
			ig to EC regulation 1272/2008 (CLP):			
	EC No: CAS No.:		EACH No:		0/ hy waight	
	INDEX no.:		hemical name: assification:		% by weight Remark:	
	200-751-6				50 - 100	
	71-36-3		utan-1-ol			
	603-004-0		lam. Liq. 3 H226 / Acute Tox. 4 H302 / 315 / Eye Dam. 1 H318 / STOT SE 3 H33			
	217-164-6				25 - 50	
	1760-24-3		-(2-Aminoethylamino)propyltrimethoxysilane			
			cute Tox. 4 H332 / Eye Dam. 1 H318 / hronic 2 H411	Skin Sens. 1 H317 / Aquatic		
	200-659-6				5 - 10	
	67-56-1		ethanol		0 10	
	603-001-0		am. Liq. 2 H225 / Acute Tox. 3 H331 / A 301 / STOT SE 1 H370	cute Tox. 3 H311 / Acute Tox. 3		
	Classifica	tion accordir	g to Directive 67/548/EEC or 1999/45/EC			
	EC No:		EACH No:			
	CAS No.:		lentification of the hazard:		% by weight	
	INDEX no		assification:		Remark:	
	200-751-6 71-36-3		utan-1-ol		50 - 100	
	603-004-0		10 / Xn; R22 / Xi; R37/38-41 / R67			
	217-164-6				25 - 50	
	1760-24-3		-(2-Aminoethylamino)propyltrimethoxysilane			
		X	n; R20 / Xi; R41 / R43 / N; R51-53			
	200-659-6				5 - 10	
	67-56-1		ethanol			

F; R11 / T; R39/23/24/25 / T; R23/24/25

Article no.: 100VR1294 Date of print: 22.01.2014 Revision date: 22.01.2014 Version: 1.2 Date of issue: 22.01.2014

EN Page:4 / 9

Additional information

Full text of R-phrases: see section 16. Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures:

General information:

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

In case of eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice.

After ingestion:

If swallowed, rinse mouth with water (only if the person is conscious). Consult physician immediately. Keep victim calm. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed:

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, Carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons: Strong water jet

5.2. Special hazards arising from the substance or mixture

Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental measures

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only

RUCO

Article no.:	100VR1294	
Date of print:	22.01.2014	Revision date: 22.01.2014
Version:	1.2	Date of issue: 22.01.2014

EN Page:5 / 9

use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air and will spread at floor level. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EC No: CAS No.:	Description:	type:	Limit va STEL (EC) TWA (
200-659-6	methanol	country.		266	mg/m3
67-56-1		EN		200	ppm
200-751-6	butan-1-ol		154		
71-36-3		EN	50		

Additional information

TWA (EC): Occupational exposure limit value

STEL (EC): Short-term occupational exposure limit value

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls:

Respiratory protection:

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection:

For prolonged or repeated handling the following glove material must be used: butyl rubber

Thickness of the glove material: > 0,4 mm ; Penetration time (maximum wearing period): > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection:

Wear closely fitting protective glasses in case of splashes.

Body protection:

Recommendation: Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures:

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Article no.: Date of print: Version:	100VR1294 22.01.2014 1.2	Revision date: 22.01.2014 Date of issue: 22.01.2014

EN Page:6 / 9

Environmental exposure controls

Do not allow to enter into surface water or drains. refer to chapter 7. No further action is necessary.

SECTION 9: Physical and chemical properties

9.1.	Information on basic physical Appearance: Physical state: Colour	and chemical properties liquid as labeled			
	Odour:	typical			
	Safety relevant basis data	() prodi	Unit	Method	Remark:
	Flash point:	27	°C	DIN 53213	
	Ignition temperature (AIT):	360	°C		
	lower explosion limit:	1,4	Vol-%		
	Upper explosion limit:	50,0	Vol-%		
	Vapour pressure at 20 °C:	128,00	mbar		
	Density at 20 °C:	0,87	g/cm³		
	Water solubility (g/l):	partial soluble			
	pH at 20 °C:	-			
	Viscosity at 20 °C	12 s 4 mm		DIN 53211	
	Solvent separation test (%):	< 3	%	ADR/RID	
	Solid content (%):	41,00	% by weight		
	solvent content:				
	Organic solvents:		% by weight		
	Water:	0	% by weight		
9.2.	Other information:				

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

Irritant and corrosive effects

Toxicological data are not available.

Sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard:

Toxicological data are not available.

Practical experience



EN Page:7 / 9

RUC

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties:

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

SECTION 12: Ecological information

Overall evaluation:

There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation:

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

Control report for waste code/ waste marking according to EAKV:

080312 waste ink containing dangerous substances

Contaminated packaging:

Recommendation:

Cleaned containers may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN-No.:

1866

14.2.	UN proper shipping name Land transport (ADR/RID): Sea transport (IMDG): Air transport (ICAO-TI / IATA-DGR):	Resin solution RESIN SOLUTION Resin solution
14.3.	Transport hazard class(es)	3
14.4.	Packing Group:	Ш

Article Date o Versio	of print:	100VR1294 22.01.2014 1.2	Revision date: 22.01.2014 Date of issue: 22.01.2014	EN Page:8 / 9			
14.5.	Environm	ental hazards:					
	Land trans	port (ADR/RID)	UMWELTGEF	ÄHRDEND			
	Marine pol	lutant:	p / 3-(2-Amino	ethylamino)propyltrimethoxysilane			
14.6.	Environm	ental hazards					
	case of an	always in closed, u accident or leaka n safe handling: se	je.	ure that persons transporting the product know what to do in			
	Further re	marks:					
	Land trans	sport (ADR/RID)					
	Tunnel res	triction code:	D/E				
	Sea trans	port (IMDG)					
	EmS-No.:		F-E, S-E				
14.7.	Special p	recautions for use	er				
	not applicable						
	SECTION 15: Regulatory information						
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation						
	VOC-value	on according to 1 e (in g/l) ISO 11890 e (in g/l) ASTM D 2)-2:	ssions of volatile organic compounds (VOC-guideline). 515,306 515,306			
	National regulations						
	Informations on working li Observe employment restric		ions under the Maternity Protection	Directive (92/85/EEC) for expectant or nursing mothers. 'juvenile work protection guideline' (94/33/EC).			

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Relevant R-and H-phrases (Number and full text):

Noicvant N-ana n-pinases (i		
Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
STOT SE 3 / H335	Specific target organ toxicity (single	May cause respiratory irritation.
	exposure)	
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Flam. Liq. 2 / H225	flammable liquids	Highly flammable liquid and vapour.
Acute Tox. 3 / H331	Acute toxicity (inhalative)	Toxic if inhaled.
Acute Tox. 3 / H311	Acute toxicity (dermal)	Toxic in contact with skin.
Acute Tox. 3 / H301	Acute toxicity (oral)	Toxic if swallowed.
STOT SE 1 / H370	Specific target organ toxicity (single	Causes damage to organs (or state all organs
	exposure)	affected, if known) (state route of exposure if it
		is conclusively proven that no other routes of
		exposure cause the hazard).
F; R11	Highly flammable	Highly flammable
T; R39/23/24/25	Toxic	Toxic: danger of very serious irreversible effects
		through inhalation, in contact with skin and if
		swallowed.
T; R23/24/25	Toxic	Toxic by inhalation, in contact with skin and if swallowed.

I RUCO

Article no.: Date of print: Version:	100VR1294 22.01.2014 1.2	Revision date: 22.01.2014 Date of issue: 22.01.2014	EN Page:9 / 9
R10			Flammable
Xn; R22		Harmful	Harmful if swallowed.
Xi; R37/3	8-41	Irritant	Irritating to respiratory system and skin. Risk of serious damage to eyes.
R67			Vapours may cause drowsiness and dizziness.
Xn; R20		Harmful	Harmful by inhalation.
Xi; R41		Irritant	Risk of serious damage to eyes.
R43			May cause sensitization by skin contact.
N; R51-53	3	Dangerous for the environment	Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.

Further remarks:

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

Remarks:

n.a. = not applicable