

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
Date of print: 09.09.2014
Version: 2.1

SERIE/SERIES
Revision date: 09.08.2014
Date of issue: 09.08.2014

EN
Page: 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers:

Article no. (manufacturer / supplier): 110GK
Identification of the substance or preparation: SERIE/SERIES

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Printing ink/
-lacquer

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/downstream user/distributor):

A.M. Ramp & Co GmbH

RUCO Druckfarben

Lorsbacher Str. 28

D-65817 Eppstein

Telephone: +49.61 98.30 40

Telefax: +49.61 98.3 22 88

Dept. responsible for information:

E-mail: info@ruco-inks.com

1.4. Emergency telephone number

Emergency telephone: +49.61 98.30 40

Only available during office hours.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to EC regulation 1272/2008 (CLP):

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226

flammable liquids

Flammable liquid and vapour.

Skin Irrit. 2 / H315

skin corrosion/irritation

Causes skin irritation.

Eye Irrit. 2 / H319

Serious eye damage/eye irritation

Causes serious eye irritation.

Skin Sens. 1 / H317

respiratory or skin sensitisation

May cause an allergic skin reaction.

Aquatic Chronic 3 / H412

Hazardous to the aquatic environment

Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or 1999/45/EC

The preparation is dangerous in the sense of Directive 1999/45/EC.

R10

Xi; R36/38

Irritant

R43

R52-53

Flammable

Irritating to eyes and skin.

May cause sensitization by skin contact.

Harmful to aquatic life. May cause long-term adverse effects in the aquatic environment.

Vapours may cause drowsiness and dizziness.

R67

2.2. Label elements

Labelling (CLP)

Hazard pictograms



Warning

Hazard statements:

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H317

May cause an allergic skin reaction.

H412

Harmful to aquatic life with long lasting effects.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
Date of print: 09.09.2014
Version: 2.1

SERIE/SERIES
Revision date: 09.08.2014
Date of issue: 09.08.2014

EN
Page:2 / 8

Safety precautions:

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use Extinguishing powder or sand for extinction.
P403 + P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to industrial incineration plant.

contains:

bisphenol A - epichlorhydrine resin, MW (700 < MW < 1000)

Supplemental Hazard information (EU):

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Labelling (67/548/EEC or 1999/45/EC)



Xi Irritant

Hazard statements:

- 10 Flammable
36/38 Irritating to eyes and skin.
43 May cause sensitization by skin contact.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Safety precautions:

- 24 Avoid contact with skin.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
37 Wear suitable gloves.
51 Use only in well-ventilated areas.

contains:

bisphenol A - epichlorhydrine resin, MW (700 < MW < 1000)

Special provisions concerning the labelling of certain mixtures

92 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

SECTION 3: Composition/ information on ingredients

3.2. Mixtures

chemical characterization (preparation)

Description: Solvent containing pigment dispersion
on resin basis

Hazardous ingredients:

Classification according to EC regulation 1272/2008 (CLP):

EC No: **REACH No:**

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
 Date of print: 09.09.2014
 Version: 2.1

SERIE/SERIES
 Revision date: 09.08.2014
 Date of issue: 09.08.2014

EN
 Page:3 / 8

CAS No.: INDEX no.:	Chemical name: classification:	% by weight Remark:
25068-38-6 603-074-00-8 259-370-9	bisphenol A - epichlorhydrine resin, MW (700 < MW < 1000) Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317	50 - 100
54839-24-6 603-177-00-8	2-ethoxy-1-methylethyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	10 - 15
203-933-3 112-07-2 607-038-00-2	01-2119475112-47-XXXX 2-butoxyethyl acetate Acute Tox. 4 H332 / Acute Tox. 4 H312	10 - 15
203-603-9 108-65-6 607-195-00-7	01-2119475791-29-XXXX 2-methoxy-1-methylethyl acetate Flam. Liq. 3 H226	5 - 10
918-668-5 64742-95-6	01-2119455851-35-xxxx hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	5 - 10

Classification according to Directive 67/548/EEC or 1999/45/EC

EC No: CAS No.: INDEX no.:	REACH No: Identification of the hazard: classification:	% by weight Remark:
25068-38-6 603-074-00-8 259-370-9	bisphenol A - epichlorhydrine resin, MW (700 < MW < 1000) Xi; R36/38 / R43	50 - 100
54839-24-6 603-177-00-8	2-ethoxy-1-methylethyl acetate R10 / R67	10 - 15
203-933-3 112-07-2 607-038-00-2	01-2119475112-47-XXXX 2-butoxyethyl acetate Xn; R20/21	10 - 15
203-603-9 108-65-6 607-195-00-7	01-2119475791-29-XXXX 2-methoxy-1-methylethyl acetate R10	5 - 10 *
918-668-5 64742-95-6	01-2119455851-35-xxxx hydrocarbons, C9, aromatics R10 / Xi; R37 / N; R51-53 / Xn; R65 / R66 / R67	5 - 10

Additional information

* Substance with a common (EC) occupational exposure limit value.
 Full text of R-phrases: see section 16.
 Full text of H-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures:

General information:

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

After inhalation

Move victim to fresh air. Put victim at rest and keep warm. In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of skin contact:

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

In case of eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice.

After ingestion:

If swallowed, rinse mouth with water (only if the person is conscious). Consult physician immediately. Keep victim calm. Do

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
Date of print: 09.09.2014
Version: 2.1

SERIE/SERIES
Revision date: 09.08.2014
Date of issue: 09.08.2014

EN
Page: 4 / 8

not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed:

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Alcohol resistant foam, Carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

Strong water jet

5.2. Special hazards arising from the substance or mixture

Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental measures

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air and will spread at floor level. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storerooms and containers:

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSIVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
Date of print: 09.09.2014
Version: 2.1

SERIE/SERIES
Revision date: 09.08.2014
Date of issue: 09.08.2014

EN
Page: 5 / 8

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

EC No: CAS No.:	Description:	type:	Limit value		Unit
			STEL (EC)	TWA (EC)	
203-933-3 112-07-2	2-butoxyethyl acetate	WEL	332 50	133 20	mg/m3 ppm
203-603-9 108-65-6	2-methoxy-1-methylethyl acetate	WEL	548 100	274 50	mg/m3 ppm

Additional information

TWA (EC): Occupational exposure limit value

STEL (EC): Short-term occupational exposure limit value

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls:

Respiratory protection:

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection:

For prolonged or repeated handling the following glove material must be used: butyl rubber

Thickness of the glove material: > 0,4 mm ; Penetration time (maximum wearing period): > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection:

Wear closely fitting protective glasses in case of splashes.

Body protection:

Recommendation: Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures:

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. refer to chapter 7. No further action is necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid
Colour: as labeled
Odour: typical

Safety relevant basis data	Unit	Method	Remark:
Flash point:	35 °C	DIN 53213	
Ignition temperature (AIT):	315 °C		
lower explosion limit:	0,8 Vol-%		
Upper explosion limit:	10,8 Vol-%		
Vapour pressure at 20 °C:	5,00 mbar		
Density at 20 °C:	1,12 g/cm³		
Water solubility (g/l):	not soluble		
pH at 20 °C:	-		
Viscosity at 20 °C	> 90 s 4 mm	DIN 53211	
Solvent separation test (%):	< 3 %	ADR/RID	
Solid content (%):	65,45 % by weight		
solvent content:			

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
Date of print: 09.09.2014
Version: 2.1

SERIE/SERIES
Revision date: 09.08.2014
Date of issue: 09.08.2014

EN
Page:6 / 8

Organic solvents: 35 % by weight
Water: 0 % by weight

9.2. **Other information:**

SECTION 10: Stability and reactivity

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

Toxicological data are not available.

Irritant and corrosive effects

Toxicological data are not available.

Sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard:

Toxicological data are not available.

Practical experience

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties:

The components in this formulation do not meet the criteria for classification as CMR category 1 or 2.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

SECTION 12: Ecological information

Overall evaluation:

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. **Toxicity**

Toxicological data are not available.

12.2. **Persistence and degradability**

Toxicological data are not available.

12.3. **Bioaccumulative potential**

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK SERIE/SERIES
Date of print: 09.09.2014 Revision date: 09.08.2014
Version: 2.1 Date of issue: 09.08.2014

EN
Page: 7 / 8

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB.

12.6. Other adverse effects

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation:

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

Control report for waste code/ waste marking according to EAKV:

080312 waste ink containing dangerous substances

Contaminated packaging:

Recommendation:

Cleaned containers may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN-No.:

1210

14.2. UN proper shipping name

Land transport (ADR/RID):

Printing ink

Sea transport (IMDG):

PRINTING INK

Air transport (ICAO-TI / IATA-DGR):

Printing ink

14.3. Transport hazard class(es)

Land transport (ADR/RID):

KEINE GÜTER DER KLASSE 3

in containers > 450 l: class 3, item 31c

Sea transport (IMDG)

3

for packages < 30 litres:

Transport in accordance with the provisions of paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI / IATA-DGR)

3

14.4. Packing Group:

III

14.5. Environmental hazards:

Land transport (ADR/RID)

n.a.

Marine pollutant:

n.a.

14.6. Environmental hazards

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further remarks:

Land transport (ADR/RID)

Tunnel restriction code:

D/E

Sea transport (IMDG)

EmS-No.:

F-E, S-D

14.7. Special precautions for user

not applicable

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article no.: 110GK
Date of print: 09.09.2014
Version: 2.1

SERIE/SERIES
Revision date: 09.08.2014
Date of issue: 09.08.2014

EN
Page: 8 / 8

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/l) ISO 11890-2: 388,009

VOC-value (in g/l) ASTM D 2369: 388,009

National regulations

Informations on working limitations:

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Relevant R-and H-phrases (Number and full text):

Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Irrit. 2 / H315	skin corrosion/irritation	Causes skin irritation.
Skin Sens. 1 / H317	respiratory or skin sensitisation	May cause an allergic skin reaction.
Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Acute Tox. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Xn; R20/21	Harmful	Harmful by inhalation and in contact with skin.
R10		Flammable
R67		Vapours may cause drowsiness and dizziness.
Xi; R37	Irritant	Irritating to respiratory system.
N; R51-53	Dangerous for the environment	Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
Xn; R65	Harmful	Harmful: may cause lung damage if swallowed.
R66		Repeated exposure may cause skin dryness or cracking.
Xi; R36/38	Irritant	Irritating to eyes and skin.
R43		May cause sensitization by skin contact.

Further remarks:

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

Remarks:

n.a. = not applicable