according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830



Article No : 110GK SERIE/SERIES

Print date 28.08.2017 Page 1 / 8 Revision date 16.10.2016 Version

SECTION 1: Identification of the substance/mixture and of the company/undertaking

product identifiers

Article No. (manufacturer/supplier): 110GK

Identification of the substance or mixture SERIE/SERIES

Relevant identified uses of the substance or mixture and uses advised against 12

Relevant identified uses:

Printing ink/ -lacquer

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

A.M. Ramp & Co GmbH

RUCO Druckfarben Telephone: +49.61 98.30 40 Lorsbacher Str. 28 Telefax: +49.61 98.3 22 88

D-65817 Eppstein

Dept. responsible for information:

E-mail info@ruco-inks.com

1.4. Emergency telephone number

Emergency telephone number +49.61 98.30 40

Only available during office hours.

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour. Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation. Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation. Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Aquatic Chronic 3 / H412 Hazardous to the aquatic environment Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms





Warning

Hazard statements

H226 Flammable liquid and vapour. Causes skin irritation. H315 H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects. H412

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves and eye/face protection. P280

P370 + P378 In case of fire, use sand, extinguishing powder or alcohol resistant foam.

P403 + P235 Store in a well-ventilated place. Keep cool.

contains:

bisphenol A - epichlorhydrine resin, MW (700 < MW < 1000) Fatty acids, C14-18- and C16-18- unsaturated, maleated

Supplemental Hazard information (EU)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 110GK SERIE/SERIES

Print date 28.08.2017 EN Version 4.3 Revision date 16.10.2016 Page 2 / 8

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description Solvent containing pigment dispersion on resin basis

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. INDEX No.	REACH No. Chemical name classification: // Remark	Wt %
25068-38-6 603-074-00-8	01-2119456619-26-XXXX bisphenol A - epichlorhydrine resin, MW (700 < MW < 1000) Eye Irrit. 2 H319 / Skin Irrit. 2 H315 / Skin Sens. 1 H317	50 - 100
259-370-9 54839-24-6 603-177-00-8	01-2119475116-39-XXXX 2-ethoxy-1-methylethyl acetate Flam. Liq. 3 H226 / STOT SE 3 H336	10 - 15
203-933-3 112-07-2 607-038-00-2	01-2119475112-47-XXXX 2-butoxyethyl acetate Acute Tox. 4 H332 / Acute Tox. 4 H312	10 - 15
203-603-9 108-65-6 607-195-00-7	01-2119475791-29-XXXX 2-methoxy-1-methylethyl acetate Flam. Liq. 3 H226	5 - 10
918-668-5 64742-95-6	01-2119455851-35-XXXX hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	5 - 10
288-306-2 85711-46-2	01-2119976378-19-XXXX Fatty acids, C14-18- and C16-18- unsaturated, maleated Skin Irrit. 2 H315 / Skin Sens. 1 H317	0,1 - 0,25

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 110GK SERIE/SERIES

Print date 28.08.2017 EN Version 4.3 Revision date 16.10.2016 Page 3 / 8

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 110GK SERIE/SERIES

Print date 28.08.2017 EN Version 4.3 Revision date 16.10.2016 Page 4 / 8

Occupational exposure limit values

2-butoxyethyl acetate

INDEX No. 607-038-00-2 / EC No. 203-933-3 / CAS No. 112-07-2

WEL, TWA: 133 mg/m3; 20 ppm WEL, STEL: 332 mg/m3; 50 ppm

Remark: (May be absorbed through the skin.)

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

WEL, TWA: 274 mg/m3; 50 ppm WEL, STEL: 548 mg/m3; 100 ppm

Additional information

TWA: long-term occupational exposure limit value STEL: short-term occupational exposure limit value

Ceiling: peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: liquid
Colour: refer to label
Odour: characteristic
Odour threshold: not determined
pH at 20 °C: not applicable
Melting point/freezing point: not determined

Initial boiling point and boiling range: 140 °C Flash point: 35 °C

Evaporation rate: not determined

Flammability (solid, gas):

burning time (s): not applicable

Upper/lower flammability or explosive limits:

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 110GK SERIE/SERIES

Print date 28.08.2017 EN Version 4.3 Revision date 16.10.2016 Page 5 / 8

Lower explosion limit: 0,8 Vol-% Upper explosion limit: 10,8 Vol-% Vapour pressure at 20 °C: 5 mbar

Vapour density: not determined

Relative density:

Density at 20 °C: 1,12 g/cm³

Solubility(ies):

Water solubility (g/L) at 20 °C: insoluble
Partition coefficient: n-octanol/water: see section 12

Ignition temperature in °C 315 °C

Decomposition temperature: not applicable

Viscosity at 20 °C: > 90 s 4 mm

Method: DIN 53211

not applicable not applicable

9.2. Other information

Solid content (%): 65,31 Wt %

solvent content:

Explosive properties: Oxidising properties:

Organic solvents: 35 Wt % Water: 0 Wt %

Solvent separation test (%): < 3 Wt % (ADR/RID)

SECTION 10: Stability and reactivity

10.1. Reactivity

Not applicable.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

Not applicable.

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification according to Regulation (EC) No 1272/2008 [CLP] No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Toxicological data are not available.

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 110GK SERIE/SERIES

Print date 28.08.2017

Version 4.3 Revision date 16.10.2016 Page 6 / 8

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP]

There is no information available on the preparation itself.

Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080312 waste ink containing dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1210

14.2. UN proper shipping name

Land transport (ADR/RID): Printing ink
Sea transport (IMDG): PRINTING INK
Air transport (ICAO-TI / IATA-DGR): Printing ink

14.3. Transport hazard class(es)

Land transport (ADR/RID): KEINE GÜTER DER KLASSE 3 in containers > 450 l: class 3, item 31c

Sea transport (IMDG)

for packages < 30 litres: Transport in accordance with the provisi ons of paragraph 2.3.2.5 of the

IMDG Cod e.

3

Air transport (ICAO-TI / IATA-DGR)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



Article No.: 110GK SERIE/SERIES

EN Page 7 / 8 Print date 28.08.2017 Revision date 16.10.2016 Version

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) not applicable not applicable Marine pollutant

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in

case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

D/E tunnel restriction code

Sea transport (IMDG)

EmS-No. F-E, S-D

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 389,619

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Eye Irrit. 2 / H319 Serious eye damage/eye irritation Causes serious eye irritation. Skin Irrit. 2 / H315 skin corrosion/irritation Causes skin irritation.

Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction. Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour. STOT SE 3 / H336 Specific target organ toxicity (single May cause drowsiness or dizziness.

exposure)

Acute Tox. 4 / H332 Acute toxicity (inhalative) Acute Tox. 4 / H312 Acute toxicity (dermal)

STOT SE 3 / H335 Specific target organ toxicity (single

exposure)

Aguatic Chronic 2 / H411 Hazardous to the aquatic environment

Asp. Tox. 1 / H304 Aspiration hazard Toxic to aquatic life with long lasting effects. May be fatal if swallowed and enters airways.

Harmful if inhaled.

Harmful in contact with skin.

May cause respiratory irritation.

Remark

n.a. = not applicable

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1.It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2015/830



110GK 28.08.2017 SERIE/SERIES Article No.:

EN Page 8 / 8 Print date Revision date 16.10.2016 Version

and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version